

# Itona TC3521-XP

## Powered by Windows XP Embedded



The Itona TC3521-XP is powered by Microsoft's Windows XP Embedded operating.

The Itona TC3521-XP boasts a very rich application set featuring ICA, RDP and UNIX Connectivity Clients, allowing swift connection to UNIX and IBM mainframes together with Microsoft servers.

Also provided is Internet Explorer 6.0 for Internet connectivity.

**This terminal can be custom configured to meet your embedded needs.**

Features & Benefits	Specifications	
<p><b>Features</b></p> <ul style="list-style-type: none"> <li>Windows XP Embedded OS</li> <li>VIA C3-800 EBGA Processor</li> <li>256MB Flash</li> <li>256MB RAM</li> <li>Terminal Services (RDP shadowing)</li> <li>VXL FlashProtect</li> <li>Citrix ICA Client v6</li> <li>Program Neighbourhood</li> <li>NFuse</li> <li>RDP Client 5.2</li> <li>Internet Explorer 6.x</li> <li>JVM</li> <li>Active X</li> <li>Shockwave</li> <li>Flash</li> <li>Windows Media Player</li> <li>Terminal Emulation Suite</li> <li>VNC</li> <li>Administration Panel</li> <li>EWF Manager</li> </ul>	<p><b>Ergonomics</b></p> <ul style="list-style-type: none"> <li>System Stand-by</li> <li>Energy saving support</li> <li>Network activity indicator (rear panel)</li> </ul> <p><b>Hardware</b></p> <ul style="list-style-type: none"> <li>VIA C3-800 Fanless CPU</li> <li>VIA PL133 North Bridge and VT8231 South Bridge</li> <li>PC133 DIMM Sockets - 1GB Max</li> <li>256MB IDE Flash</li> <li>256MB RAM</li> </ul> <p><b>Graphics &amp; Audio</b></p> <ul style="list-style-type: none"> <li>Up to 1600x1200 resolution</li> <li>32bit Color support</li> <li>Up to 85Hz refresh</li> <li>Integrated Trident Blade 3D Graphics core</li> <li>2 Channel AC'97 Codec</li> </ul> <p><b>Networking</b></p> <ul style="list-style-type: none"> <li>10/100 Fast Ethernet</li> <li>Auto speed sensing</li> </ul> <p><b>External Ports</b></p> <ul style="list-style-type: none"> <li>10/100 Fast Ethernet Autosensing</li> <li>Serial port</li> <li>Bi-directional parallel port</li> <li>Four USB ports (1.1)</li> <li>Stereo out</li> <li>Line in</li> <li>Mic In</li> <li>VGA Display</li> <li>PS/2 Keyboard</li> <li>PS/2 Mouse</li> <li>Power in</li> <li>Power Out (for Monitor)</li> </ul>	<p><b>Internal IO</b></p> <ul style="list-style-type: none"> <li>IDE Flash</li> </ul> <p><b>Power</b></p> <ul style="list-style-type: none"> <li>Internal power supply</li> <li>Voltage: 90-260v AC</li> <li>Frequency: 50~60Hz</li> </ul> <p><b>Regulatory</b></p> <ul style="list-style-type: none"> <li>CE</li> <li>TUV</li> <li>UL/ULC</li> <li>FCC-B</li> <li>CTICK</li> <li>CBA</li> </ul> <p><b>Mechanical</b></p> <ul style="list-style-type: none"> <li>240 (H) x 267 (D) x 50 (W) mm</li> </ul>