

# Percio TC5131-LI

Powered by Gio Linux



The Percio TC5131-LI is designed to take as little space as possible on the corporate desktop where space is premium.

The ergonomic design together with the powerful processor and external ports such as dual USB and printer ports make the Percio TC5131-LI the ideal thin client appliance.

The Percio TC5131-LI comes complete with ICA, RDP, X-Windows and UNIX/IBM emulators.

(This product previously called TC5000-LI)

Features & Benefits	Specifications	
<p><b>Features</b></p> <ul style="list-style-type: none"> <li>❖ Gio Linux operating system</li> <li>❖ Supports Citrix, Windows NT-TSE, Windows 2000/2003, UNIX and X-Windows servers</li> <li>❖ Embedded ICA Client</li> <li>❖ Embedded RDP Client</li> <li>❖ XDM</li> <li>❖ REXEC</li> <li>❖ Thinprint</li> <li>❖ PPP</li> <li>❖ USB ( FDD, PRN, KBD and Mouse)</li> <li>❖ SMB printing</li> <li>❖ LPD printing support</li> <li>❖ VNC</li> <li>❖ NFS/XFS Font Server Mapping</li> <li>❖ NFS / SMB (File sharing)</li> <li>❖ Local flash boot means fast start up</li> <li>❖ Dual USB</li> <li>❖ PS/2 keyboard port</li> <li>❖ PS/2 mouse port</li> <li>❖ Parallel printer port</li> <li>❖ Stereo Sound</li> <li>❖ 10/100 Fast Ethernet</li> <li>❖ 1280x1024 resolution up to 16 bit</li> <li>❖ No moving parts</li> <li>❖ 64MB RAM</li> <li>❖ Easy insert Compact Flash for OS</li> <li>❖ Accepts standard keyboard and mouse</li> <li>❖ Centrally managed using InControl software</li> </ul>	<p><b>Ergonomics</b></p> <ul style="list-style-type: none"> <li>❖ Energy saving support</li> <li>❖ Network activity indicator</li> </ul> <p><b>Hardware</b></p> <ul style="list-style-type: none"> <li>❖ SIS 550 Processor</li> <li>❖ 64MB Memory</li> <li>❖ 32MB Flash</li> </ul> <p><b>Setup</b></p> <ul style="list-style-type: none"> <li>❖ Mouse and keyboard driven</li> <li>❖ User friendly</li> <li>❖ Password protected</li> <li>❖ Allows automatic login</li> </ul> <p><b>Graphics</b></p> <ul style="list-style-type: none"> <li>❖ Up to 1280x1024 resolution (up to 85Hz)</li> <li>❖ Up to 65535 Colors</li> </ul> <p><b>Networking</b></p> <ul style="list-style-type: none"> <li>❖ 10/100 Fast Ethernet</li> <li>❖ Auto speed sensing</li> </ul> <p><b>External Ports</b></p> <ul style="list-style-type: none"> <li>❖ 10/100 Fast Ethernet Autosensing</li> <li>❖ PS/2 Keyboard &amp; Mouse ports</li> <li>❖ Dual USB ports</li> <li>❖ Parallel Printer port</li> <li>❖ VGA Display</li> <li>❖ Power in</li> </ul> <p><b>Power</b></p> <ul style="list-style-type: none"> <li>❖ External power supply</li> <li>❖ Voltage: 100–240VAC</li> <li>❖ Frequency: 50–60Hz</li> <li>❖ Consumption: 10W</li> </ul>	<p><b>Regulatory</b></p> <ul style="list-style-type: none"> <li>❖ CE mark</li> <li>❖ FCC B</li> <li>❖ UL1950</li> <li>❖ ULC</li> <li>❖ TUV</li> <li>❖ GS</li> <li>❖ EN60950</li> <li>❖ IEC950</li> <li>❖ CISPR22</li> </ul> <p><b>Mechanical</b></p> <ul style="list-style-type: none"> <li>❖ 194.5 x 151.5 x 40 (mm)</li> <li>❖ Weight 0.65 Kg</li> </ul> <p><b>Environmental</b></p> <ul style="list-style-type: none"> <li>❖ Operating : 5 °C to 40 °C (41 °F to 104 °F)</li> <li>❖ Storage : -40 °C to 60 °C (-4 °F to 140 °F)</li> <li>❖ 90% maximum, non-condensing</li> </ul>