

Percio TC5141-CE

Powered by Windows CE.net



The Percio TC5141-CE is designed to take as little space as possible on the corporate desktop where space is premium.

The ergonomic design together with the powerful processor and external ports such as dual USB and printer ports make the Percio TC5141-CE the ideal thin client appliance.

The Percio TC5141-CE comes complete with ICA, RDP, UNIX/IBM emulators and Internet Explorer browser.

Features & Benefits	Specifications	
<p>Features</p> <ul style="list-style-type: none"> Microsoft Windows CE operating system Microsoft RDP Embedded Client Citrix ICA Embedded Client Ericom Terminal Emulation Suite Internet Explorer ThinPrint Equipped with dual USB, standard printer 10/100 Fast Ethernet High 1280x1024 resolution No moving parts 64MB RAM + 32MB Flash Stereo sound Centrally managed using InControl <p>Benefits</p> <ul style="list-style-type: none"> Microsoft's industry standard, Windows CE operating system Fast and simple connection to Windows 2000/2003 Servers and legacy Windows NT-TSE technology Use instantly with Windows NT-TSE, Windows 2000, Windows XP, Citrix Systems MetaFrame and WinFrame operating environments InControl management software allows administrators to deploy devices with speed and ease. InControl also allows the reliable remote update of firmware and settings to single or multiple devices Small footprint means low space usage Quiet, reliable and durable - no moving parts 	<p>Ergonomics</p> <ul style="list-style-type: none"> Energy saving support Network activity indicator <p>Hardware</p> <ul style="list-style-type: none"> SIS 550 Processor 64MB DIMM Memory (128MB Max) Disk-on-Chip/Compact Flash Medium <p>Setup</p> <ul style="list-style-type: none"> Mouse and keyboard driven User friendly Password protected Allows automatic login <p>Graphics</p> <ul style="list-style-type: none"> Up to 1280x1024 resolution (up to 85Hz) Up to 65535 Colors <p>Networking</p> <ul style="list-style-type: none"> 10/100 Fast Ethernet Auto speed sensing <p>External Ports</p> <ul style="list-style-type: none"> 10/100 Fast Ethernet Autosensing PS/2 Keyboard & Mouse ports Dual USB ports Parallel Printer port VGA Display Power in <p>Power</p> <ul style="list-style-type: none"> External power supply Voltage: 100~240VAC Frequency: 50~60Hz Consumption: 10W 	<p>Regulatory</p> <ul style="list-style-type: none"> CE mark FCC B UL1950 ULC TUV GS EN60950 IEC950 CISPR22 <p>Mechanical</p> <ul style="list-style-type: none"> 194.5 x 151.5 x 40 (mm) Weight 0.65 Kg <p>Environmental</p> <ul style="list-style-type: none"> Operating : 5 °C to 40 °C (41 °F to 104 °F) Storage : -40 °C to 60 °C (-4 °F to 140 °F) 90% maximum, non-condensing