

Percio TC5231-LI

Powered by Gio Linux



Monitor & keyboard for illustration only

The Percio TC5231-LI is designed to take as little space as possible on the corporate desktop where space is premium.

The ergonomic design together with the powerful processor and external ports such as dual USB and printer ports make the Percio TC5231-LI the ideal thin client appliance.

The Percio TC5231-LI comes complete with ICA, RDP, X-Windows and UNIX/IBM emulators.

Features & Benefits	Specifications	
<p>Features</p> <ul style="list-style-type: none"> Gio Linux operating system Supports Citrix, Windows NT-TSE, Windows 2000/2003, UNIX and X-Windows servers Embedded ICA Client Embedded RDP Client Embedded Tarantella Client Netscape Navigator (No JVM) XDM REXEC Thinprint PPP USB (FDD, PRN, KBD and Mouse) SMB printing LPD printing support VNC NFS/XFS Font Server Mapping NFS / SMB (File sharing) Local flash boot means fast start up Stereo Sound No moving parts Compact Flash for OS Accepts standard keyboard and mouse Centrally managed using InControl software 	<p>Ergonomics</p> <ul style="list-style-type: none"> Energy saving support Network activity indicator <p>Hardware</p> <ul style="list-style-type: none"> SIS 550 Processor 64MB Memory 32MB Flash <p>Setup</p> <ul style="list-style-type: none"> Mouse and keyboard driven User friendly Password protected Allows automatic login <p>Graphics</p> <ul style="list-style-type: none"> Max 1280x1024 resolution (up to 85Hz) Max 65535 color h/w support <p>Networking</p> <ul style="list-style-type: none"> 10/100 Fast Ethernet Auto speed sensing <p>External Ports</p> <ul style="list-style-type: none"> 10/100 Fast Ethernet Autosensing PS/2 Keyboard & Mouse ports Dual USB ports Parallel Printer port Serial port PCMCIA PCI Slot VGA Display Power in <p>Power</p> <ul style="list-style-type: none"> Internal power supply Voltage: 100~240VAC Frequency: 50~60Hz Consumption: 15W 	<p>Regulatory</p> <ul style="list-style-type: none"> CE mark FCC B UL1950 ULC TUV GS EN60950 IEC950 CISPR22 <p>Mechanical</p> <ul style="list-style-type: none"> 246 x 177 x 48 (mm) Weight 1,50 Kg <p>Environmental</p> <ul style="list-style-type: none"> Operating : 5 °C to 40 °C (41 °F to 104 °F) Storage : -40 °C to 60 °C (-4 °F to 140 °F) 90% maximum, non-condensing